

TECHNICAL INFORMATION

WaxRemover



Remover solvent based for oiled and waxed floors. Dissolves heavy soilings and old care layers.

- Classic intensive cleaner for oiled / waxed floors
- Also suitable for water-sensitive flooring

Range of use:

Suitable for removing old layers of wax from oiled and waxed floor coverings.

Technical Data

Art.-no.

10309



1 l

12 l



6

-



480

50

Contents

> 30% aliphatic hydrocarbons, perfumes, LIMONENE

Storage and transportation

36 months of storage stability. Not sensitive to frost.

GISCODE

GG0

Application

- Shake the contents well.
- Observe the general and, if available, the product-specific health and safety instructions. More specific information relating to GISCODE can be found in the usage instructions, which are available at www.wingis-online.de.

Thinner

The product is supplied ready for use and must not be diluted!

Application tool/application rate

LOBATOOL spray can / 20-40 ml/m² = 25-50m²/l depending on the degree of soiling. Cleaning with a single-disc machine and LOBATOOL special pad green, remove loosened dirt with a cloth.



Application

Application:

Apply WaxRemover with a cloth or LOBATool spray can to the surface being cleaned. After a short time, process the surface with a single-disc machine with a LOBATool special pad green underneath. The dissolved wax and dirt residue must be then wiped up immediately with a dry cloth. Work in sections on larger areas.

Repeat this process if necessary.

Carefully ventilate work areas while the product is being used and while the areas are drying.

General guidelines

Safety notes: Flammable solvent vapours emerge during the drying process when working with products containing high quantities of solvents. As a result, fire, naked light, welding, smoking and so on are prohibited in the immediate vicinity of such products. Ventilate working areas and storage rooms well. Electrical equipment in workrooms and ancillary rooms must be switched off in sufficient time to ensure that they are cold when work begins. Any spark generation, including on electrical equipment, must be avoided. Keep material containers tightly closed. Solvent sensitive components, plants or animals (fish tanks) must be removed from areas at risk of exposure to solvent vapours.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and relate to Spezial conditions. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice by speaking to the LOBA application engineering department. Observe the floor covering manufacturer's recommendations and the provisions of the current standards. Our liabilities and responsibilities are exclusively in accordance with our Terms and Conditions and are not extended by this information or by our advice. The publishing of a new technical data sheet automatically invalidates the earlier version.

Drying time: The indicated drying times are valid for +20°C and 55% to 65% relative humidity, and assume careful, draught-free ventilation of the working area. Lower temperatures, higher relative humidity or poorer ventilation lead to longer drying times. Do not apply any protective coverings, wet clean the surface or lay carpet until the coating has achieved its final hardening. Product-specific data can be found in the relevant technical information.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.

